



BASAK



4105 STAGE V



The photographs and the technical specifications used may include optional features. BAŞAK Tractor reserves the right to modify the technical specifications in this brochure. (17.10.2025)

ASKO Sınai ve Teknolojileri Üretim Sanayi Tic. A.Ş.
Başak Traktör Şubesi

Hanlı Sakarya Mah. Başak Sok. No:65 Arifiye / SAKARYA / TÜRKİYE
WhatsApp / Viber : +90 537 234 78 67
export@basaktraktor.com.tr



A MEMBER OF



CORPORATION

f basaktraktortr

ig basaktraktor

in basaktraktor

x basaktraktortr

yt basaktraktortr

www.basaktraktor.com

www.asko.com.tr

4105**STAGE V****ENGINE**

Engine Type		BAŞAK 3.6
Emission Level		EU STAGE V
Aspiration		Turbo-Intercooler
Cylinder Volume-Number of Cylinders	cm ³ /adet	3,621/4
Maximum Engine Power	kw/hp/rpm	74,4/102/2200
Maximum Engine Torque	nm / rpm	420/1600
Injection System		Common Rail
Fuel	L	120

TRANSMISSION

Gearbox Type		Mechanically Synchronized
Speed Options 24+24 (Crawler Transmission Included)		Option
Speed Options 16+16		Option
Crawler Transmission		Option
Power-Shuttle	km/h	Mechanic Shuttle
4 WD Control Drive		Electro-Hydraulic
Front Differentials Lock		Limited Slip Differential (Automatic)
Rear Differential Control Drive		Electro-Hydraulic

HYDRAULIC SYSTEM

Maximum Oil Flow-Pump Pressure	(L/dk)/bar	50/200
Functions		Mechanic
Hydraulic Output	çıkış/valf	6/3 (Mekanik) - 8/4 (3M-1E) - 8/4 (3M Float-1E)
Maximum Rear Hitch Lifting Capacity	kg	3.500

PTO SHAFT / ZAPFWELLE

Type		Independent Double Speed, (Opt 4 Speed) - Mechanical Control
Wheel Speed Synchronized PTO Speed		Option
PTO Clutch		Mechanic
PTO Shift	rpm	540-540E (Opt. 540-540E-1000-1000E)

BRAKES

Service Brake		Oil Immersed Multi Disc Brake
Four Wheel Breaking System		Standard
Foot Brake		Hydraulic Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	340/85R24 - 420/85R34
2nd Option	front-rear	340/85R24 - 460/85R30
3rd Option	front-rear	340/85R24 - 340/85R38

WEIGHTS

Total Length	mm	4265
Total Height	mm	2695-2724
Wheelbase	mm	2444
Front Track Width	mm	1510
Rear Track Width	mm	1580-1610
Ground Clearance	mm	362-409

MEASURES

Tractor Weight	kg	4570
Front Ballast Weight	kg	8x30+50
Rear Ballast Weight	kg	4x45

EQUIPMENT

Ledbar		Option
Battery Circuit Breaker		Standard
Hydraulic Top Link		Option
Rear View Camera-Screen		Option