



BASAK



2060 BT



The photographs and the technical specifications used may include optional features.
BASAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.ş BASAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



f basaktraktortr

@ basaktraktor

in basaktraktor

www.basaktraktor.com.tr

basaktraktortr

basaktraktortr

www.asko.com.tr

2060 BT



ENGINE

Engine Type		SONALIKA ITL 3100 FLT
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Maximum Engine Power	cm ³ /pcs	2780/3
Nominal Engine Power	kW/hp/rpm	43/58/2100
Nominal Engine Power	kW/hp/rpm	43/58/2100
Maximum Engine Torque	Nm/rpm	230/1300
Cooling System		Water Cooled
Fuel Tank	L	72

TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Gearbox		12+12
Maximum - Minimum Speed	Km/h	1.90-39.12
Four Wheel Drive		Mechanic
Front Differential Lock		Limited slip
Rear Differential Lock		Mechanical Control
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

HYDRAULIC SYSTEM

Functions		Mechanically Controlled, Position, Towing - Sensitivity
Hydraulic Output	output/valve	4/2
Maximum Rear Hitch Lifting Capacity	kg	2.600
Three-Point Hitch System Class		Category II

PTO SHAFT

Type		Independent Double Speed
PTO Speed		Electro-Hydraulic
PTO rpm Synchronized to Wheel rpm	rpm	540 (1953) - 540E (1506)

BRAKES

Service Brake		Oil Immersed Multi Disc Brake
Foot Brake		Mechanical Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	280/85R20 - 13,6-36
2nd Option	front-rear	260/80R20 - 14,9-30
3rd Option	front-rear	280/85R20 - 340/85R36
4th Option	front-rear	260/80R20 - 380/85R30

DIMENSIONS

Total Length (Including Front Weights)	mm	3970
Total Height	mm	2790
Wheelbase	mm	2178
Front Track Width	mm	1370-1490
Rear Track Width	mm	1375-1512
Ground Clearance	mm	410

WEIGHTS

Tractor Weight (Without Additional Weight)	kg	2.840
Front Weights	kg	4x30+50
Rear Weights	kg	2x45