



# BASAK



## 5075 BB



The photographs and the technical specifications used may include optional features.  
BASAK Tractor reserves the right to modify the technical specifications in this brochure.

**ASKO Sınai Ve Tek. San. Tic A.ş BASAK Traktör Şube**  
Hanlı Sakarya Mh. Başak Sk No:65  
Arifiye/SAKARYA/TÜRKİYE  
Tel: +90 264 295 83 00  
info@basaktraktor.com.tr



f basaktraktortr

@ basaktraktor

in basaktraktor

x basaktraktortr

yt basaktraktortr

[www.basaktraktor.com.tr](http://www.basaktraktor.com.tr)

[www.asko.com.tr](http://www.asko.com.tr)

# 5075 BB



## ENGINE

|                                       |                      |                                    |
|---------------------------------------|----------------------|------------------------------------|
| Engine Type                           |                      | DEUTZ TCD 2.2                      |
| Emission Level                        |                      | EU STAGE V                         |
| Aspiration                            |                      | Turbo-Intercooler                  |
| Cylinder Volume / Number of Cylinders | cm <sup>3</sup> /pcs | 2,194/3                            |
| Maximum Engine Power                  | kW/hp/rpm            | 55/75/2600                         |
| Maximum Engine Torque                 | Nm/rpm               | 280/1600                           |
| Air Filter Type                       |                      | Pre-Cleaner 2 Stage Dry Air Filter |
| Injection System                      |                      | Common Rail                        |
| Fuel Tank                             | L                    | 56                                 |

## TRANSMISSION

|                            |  |                    |
|----------------------------|--|--------------------|
| Gearbox Type               |  | 16+8               |
| 4 WD Control               |  | Electro-Hydraulic  |
| Front Differential Control |  | Limited Slip       |
| Rear Differential Control  |  | Mechanical Control |

## HYDRAULIC SYSTEM

|                                     |              |                  |
|-------------------------------------|--------------|------------------|
| Maximum Oil Flow / Pump Pressure    | lpm/bar      | 50/200           |
| Functions                           |              | Mechanic         |
| Hydraulic Output                    | output/valve | 4/2-(6/3 Option) |
| Maximum Rear Hitch Lifting Capacity | kg           | 2.400            |
| Auto-Lift                           |              | Mechanic         |

## PTO SHAFT

|                        |              |                                                                      |
|------------------------|--------------|----------------------------------------------------------------------|
| Type                   |              | 2 Speed PTO, Electro Hydraulic Controlled                            |
| PTO Speed              |              | 540-540E                                                             |
| Front Linkage System   |              | Option, Capacity 1.300 kg                                            |
| Front Hydraulic Output | output/valve | Option, 2/1                                                          |
| Front PTO              |              | Option, 6 Spline Multidisc Dry Clutch, With Sintered Friction Lining |
| Front PTO Speed        | rpm          | 1000 CCW (@1970 rpm Engine Speed)                                    |

## BRAKES

|                           |  |                               |
|---------------------------|--|-------------------------------|
| Service Brake             |  | Oil Immersed Multi Disc Brake |
| Four Wheel Braking System |  | Standard                      |
| Foot Brake                |  | Hydraulic Control             |
| Parking Brake             |  | Mechanical Control            |

## TIRE OPTIONS

|            |            |                       |
|------------|------------|-----------------------|
| 1st Option | front-rear | 260/70R16 - 380/70R24 |
| 2nd Option | front-rear | 280/70R18 - 380/70R28 |
| 3rd Option | front-rear | 260/70R16 - 360/70R24 |

## WEIGHTS AND MEASURES

|                                            |    |       |
|--------------------------------------------|----|-------|
| Tractor Weight (Without Additional Weight) | kg | 2.900 |
| Front Ballast Weight                       | kg | 6x35  |
| Rear Ballast Weight                        | kg | 2x50  |
| Total Length                               | mm | 3670  |
| Wheelbase                                  | mm | 2049  |
| Total Width                                | mm | 1665  |
| Total Height                               | mm | 2396  |
| Front Track Width                          | mm | 1355  |
| Rear Track Width                           | mm | 1280  |
| Ground Clearance                           | mm | 300   |

## ACCESSORIES

|                         |  |          |
|-------------------------|--|----------|
| Battery Circuit Breaker |  | Standard |
| Follow Me Home          |  | Option   |
| Hydraulic Top Link      |  | Option   |