



BASAK



2075 BK CABIN



The photographs and the technical specifications used may include optional features.
BASAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.Ş. BAŞAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



A MEMBER OF



ASKO

CORPORATION

basaktraktortr

basaktraktor

basaktraktor

basaktraktortr

basaktraktortr

www.basaktraktor.com.tr

www.asko.com.tr

2075 BK CABIN



ENGINE

Engine Type		BT40845T3
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm ³ /pcs	3142/4
Maximum Engine Power	kW/hp/rpm	53/72/2500
Nominal Engine Power	kW/hp/rpm	53/72/2500
Maximum Engine Torque	Nm/rpm	273/1600
Cooling System		Water Cooled
Fuel Tank	L	72

TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Gearbox		16+8
4WD Control		Electro-Hydraulic
Front Differential Lock		Limited Slip
Rear Differential Lock		Mechanical Control
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

HYDRAULIC SYSTEM

Functions		Mechanical Control, Position, Towing-Sensitivity
Hydraulic Output	output/valve	4/2
Maximum Rear Hitch Lifting Capacity	kg	3.000
Three Point Linkage System Class		Category II

PTO SHAFT

Type		Independent Double Speed
PTO Clutch		Electro-Hydraulic
PTO Speed (Engine Speed)	rpm	540 (1953) - 540E (1506)

BRAKES

Type		Oil Immersed Multi Disc Brake
Foot Brake		Mechanical Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	11,2-24 - 16,9-30
2nd Option	front-rear	11,2-24 - 18,4-30
3rd Option	front-rear	11,2-24 - 13,6-38

DIMENSIONS

Total Length (Including Front Weights)	mm	3930
Total Height	mm	2555
Wheelbase	mm	2205
Front Track Width	mm	1250-1380
Rear Track Width	mm	1320-1520
Ground Clearance	mm	460

WEIGHTS

Tractor Weight (Without Additional Weight)	kg	3.285
Front Weights	kg	6x30+50
Rear Weights	kg	4x45