



# BASAK



## 2105 S



The photographs and the technical specifications used may include optional features.  
BASAK Tractor reserves the right to modify the technical specifications in this brochure.

**ASKO Sınai Ve Tek. San. Tic A.ş BASAK Traktör Şube**  
Hanlı Sakarya Mh. Başak Sk No:65  
Arifiye/SAKARYA/TÜRKİYE  
Tel: +90 264 295 83 00  
info@basaktraktor.com.tr



A MEMBER OF



[f basaktraktortr](#)

[@ basaktraktor](#)

[in basaktraktor](#)

[www.basaktraktor.com.tr](http://www.basaktraktor.com.tr)

[x basaktraktortr](#)

[yt basaktraktortr](#)

[www.asko.com.tr](http://www.asko.com.tr)

# 2105 S



## ENGINE

Engine Type		PERKINS - 1104D-44TA
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm <sup>3</sup> /pcs	4400/4
Maximum Engine Power	kW/hp/rpm	75/102/2200
Nominal Engine Power	kW/hp/rpm	75/102/2200
Maximum Engine Torque	Nm/rpm	405/1400
Cooling System		Water Cooled
Fuel Tank	L	120

## TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Shuttle (Synchronizer)		Standard Synchromesh
Gearbox		24+24
Creeper		Standard
Maximum - Minimum Speed	Km/h	0,48-40
4WD Control		Electro-Hydraulic
Front Differential Lock		Limited Slip
Rear Differential Lock		Electro-Hydraulic
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

## HYDRAULIC SYSTEM

Functions		Mechanical Control, Position, Towing-Sensitivity
Hydraulic Output	output/valve	6/3
Maximum Rear Hitch Lifting Capacity	kg	3.400
Three Point Linkage System Class		Category II

## PTO SHAFT

Type		Independent Four - Speed
PTO rpm Synchronized to Wheel rpm		Standard
PTO Clutch		Electro-Hydraulic
PTO Speed (Engine Speed)	rpm	430 (2073) - 540 (1881) - 540E (1530) - 1000 (2048)

## BRAKES

Type		Oil Immersed Multi Disc Brake
Foot Brake		Hydraulic Control
Parking Brake		Mechanical Control

## TIRE OPTIONS

1st Option	front-rear	340/85R24 - 420/85R34
2nd Option	front-rear	340/85R24 - 340/85R38
3rd Option	front-rear	320/85R28 - 380/85R38

## DIMENSIONS

Total Length (Including Front Weights)	mm	4355
Total Height	mm	2783-2807
Wheelbase	mm	2445
Front Track Width	mm	1510
Rear Track Width	mm	1500-1700
Ground Clearance	mm	355

## WEIGHTS

Tractor Weight (Without Additional Weight)	kg	3.900
Front Weights	kg	8x30+50
Rear Weights	kg	4x45

## ACCESSORIES

Ledbar		Standard
Air Compressor		Standard
Hydraulic Top Link		Standard
Rear View Camera		Option