BAŞAK

2060 BB

The photographs and the technical specifications used may include optional features.
BAŞAK Tractor reserves the right to modify the technical specifications in this brochure.

A MEMBER OF

ASKO
CORPORATION

basaktraktortr   basaktraktor   basaktraktor
basaktraktortr   basaktraktortr

www.basaktraktor.com.tr

www.asko.com.tr

2060 BB

ENGINE

Engine Type		SONALIKA ITL 3100 FLT
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm³/pcs	2780/3
Maximum Engine Power	kW/hp/rpm	43/58/2100
Nominal Engine Power	kW/hp/rpm	43/58/2100
Maximum Engine Torque	Nm/rpm	230/1300
Cooling System		Water Cooled
Fuel Tank	L	85

TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Gearbox		16+8
4WD Control		Electro-Hydraulic
Front Differential Lock		Limited Slip
Rear Differential Lock		Mechanical Control
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

HYDRAULIC SYSTEM

Functions		Mechanical Control, Position, Towing-Sensitivity
Hydraulic Output	output/valve	4/2
Maximum Rear Hitch Lifting Capacity	kg	2.600
Three Point Linkage System Class		Category II

PTO SHAFT

Type		Independent Double Speed
PTO Clutch		Electro-Hydraulic
PTO Speed (Engine Speed)	rpm	540 (1953) - 540E (1506)

BRAKES

Type		Oil Immersed Multi Disc Brake
Foot Brake		Mechanical Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	260/70R16 - 380/70R24
2nd Option	front-rear	260/70R18 - 380/70R28

DIMENSIONS

Total Length (Including Front Weights)	mm	3880
Total Height	mm	2510
Wheelbase	mm	2040
Front Track Width	mm	1340
Rear Track Width	mm	1285
Ground Clearance	mm	235-275

WEIGHTS

Tractor Weight (Without Additional Weight)	kg	2.660
Front Weights	kg	6x30+50
Rear Weights	kg	2x50