



BASAK



2055 COMPACT



The photographs and the technical specifications used may include optional features.
BASAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.ş BASAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



A MEMBER OF



ASKO

CORPORATION

basaktraktortr

basaktraktor

basaktraktor

www.basaktraktor.com.tr

basaktraktortr

basaktraktortr

www.asko.com.tr

2055 COMPACT



ENGINE

Engine Type		SONALIKA ITL 3100 FLT
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm ³ /pcs	2780/3
Maximum Engine Power	kW/hp/rpm	43/58/2100
Nominal Engine Power	kW/hp/rpm	43/58/2100
Maximum Engine Torque	Nm/rpm	230/1300
Cooling System		Water Cooled
Fuel Tank	L	65

TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Gearbox		8+8
Maximum - Minimum Speed	Km/h	2.03-32.02
4WD Control		Electro-Hydraulic
Front Differential Lock		Limited Slip
Rear Differential Lock		Mechanical Control
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

HYDRAULIC SYSTEM

Functions		Mechanical Control, Position, Towing-Sensitivity
Hydraulic Output	output/valve	4/2
Maximum Rear Hitch Lifting Capacity	kg	2.700
Three Point Linkage System Class		Category II

PTO SHAFT

Type		Independent Double Speed
PTO Clutch		Electro-Hydraulic
PTO Speed (Engine Speed)	rpm	540 (1953) - 540E (1506)

BRAKES

Type		Oil Immersed Multi Disc Brake
Foot Brake		Mechanical Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	280/70R18 - 14,9-28
2nd Option	front-rear	280/70R18 - 380/85R28

DIMENSIONS

Total Length (Including Front Weights)	mm	3850
Total Height	mm	2615
Wheelbase	mm	1940
Front Track Width	mm	1390
Rear Track Width	mm	1380
Ground Clearance	mm	315

WEIGHTS

Tractor Weight (Without Additional Weight)	kg	2.860
Front Weights	kg	4x30+50
Rear Weights	kg	2x45