



BASAK



5115 *Red Power*



The photographs and the technical specifications used may include optional features.
BAŞAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.ş BAŞAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



A MEMBER OF



[f basaktraktortr](#)

[@ basaktraktor](#)

[in basaktraktor](#)

www.basaktraktor.com.tr

[x basaktraktortr](#)

[v basaktraktortr](#)

www.asko.com.tr



ENGINE

Engine Type		DEUTZ TCD 3.6
Emission Level		EU STAGE V
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm ³ /pcs	3,621/4
Maximum Engine Power	kW/hp/rpm	87/119/2000
Nominal Engine Power	kW/hp/rpm	83/113/2200
Maximum Engine Torque	Nm/rpm	476/1600
Air Filter Type		Pre-Cleaner 2 Stage Dry Air Filter
Injection System		Common Rail
Fuel / AdBlue Tank	L	120/20

TRANSMISSION

Gearbox Type		24+24 Mechanic
Shuttle		Mechanic Shuttle
4WD Control		Power Hi-Lo (2 Stage)
Front Differential Control Drive		Electro-Hydraulic
Rear Differential Control Drive		Limited Slip

HYDRAULIC SYSTEM

Maximum Oil Flow / Pump Pressure	lpm/bar	70/200
Functions		Electronic
Hydraulic Output	output/valve	8/4 (6/3 Option)
Maximum Rear Hitch Lifting Capacity	kg	4500
Rear Hitch Remote Controls on Fenders		Standard
Auto-Lift		Electronic

PTO SHAFT

Type		Independent Double Speed (Wet Clutch PTO)
PTO Speed		540-540E / (540-1000 Option)
Front Linkage System		Option, Capacity 2.200 kg
Front Hydraulic Output	output/valve	Option, 2/1
Front PTO		Option, 6 Spline Multidisc Dry Clutch, With Sintered Friction Lining
Front PTO Speed	rpm	1000 CCW (@2000rpm Engine Speed)

BRAKES

Service Brake		Oil Immersed Multi Disc Brake
Foot Brake		Hydraulic Control
Parking Brake		Mechanical Control
Four Wheel Braking System		Standard

TIRE OPTIONS

1st Option	front-rear	380/85R24 - 380/85R38
2nd Option	front-rear	320/85R28 - 380/85R38
3rd Option	front-rear	340/85R24 - 420/85R34
4th Option	front-rear	440/65R24 - 540/65R34
5th Option	front-rear	380/70R28 - 460/85R34
6th Option	front-rear	340/85R24 - 480/70R34

WEIGHTS AND MEASURES

Tractor Weight (Without Additional Weight)	kg	4960-5340
Front Ballast Weight	kg	12x40+70
Rear Ballast Weight	kg	6x45
Total Length (Additional Weightless)	mm	4622-4840
Wheelbase	mm	2500
Total Width	mm	1990-2490
Total Height	mm	2695-2745
Front Track Width	mm	1632-1974
Rear Track Width	mm	1610-2022
Ground Clearance	mm	360-510

ACCESSORIES

Battery Circuit Breaker		Standard
Hydraulic Top Link		Standard
Air Compressor		Standard
Pneumatic Trailer Brake		Option (Maximum Towable Mass 28 Tons)
Sunroof		Option
Cabin Suspension		Option
Pneumatic Seat		Option
Automatic Trailer Hitch		Option
Ledbar		Option
Rear View Camera		Option