



BASAK



2080 BB CABIN



The photographs and the technical specifications used may include optional features.
BAŞAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.Ş BAŞAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



f basaktraktortr

@ basaktraktor

in basaktraktor

x basaktraktortr

you basaktraktortr

www.basaktraktor.com.tr

www.asko.com.tr

2080 BB CABIN



ENGINE

Engine Type		PERKINS 1103D 33TA
Emission Level		EU STAGE IIIA
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm³/pcs	3300/3
Maximum Engine Power	kW/hp/rpm	58/79/2200
Nominal Engine Power	kW/hp/rpm	58/79/2200
Maximum Engine Torque	Nm/rpm	310/1400
Cooling System		Water Cooled
Fuel Tank	L	70

TRANSMISSION

Gearbox Type		Mechanical Synchromesh
Gearbox		16+8
4WD Control		Electro-Hydraulic
Front Differential Lock		Limited Slip
Rear Differential Lock		Mechanical Control
Gearbox Clutch		Double Disc Dry Type (Independent Control for PTO)

HYDRAULIC SYSTEM

Functions		Mechanical Control, Position, Towing-Sensitivity
Hydraulic Output	çıkış/valf	4/2
Maximum Rear Hitch Lifting Capacity	kg	3.000
Three Point Linkage System Class		Category II

PTO SHAFT

Type		Independent Double Speed
PTO Clutch		Electro-Hydraulic
PTO Speed (Engine Speed)	rpm	540 (1953) - 540E (1506)

BRAKES

Type		Oil Immersed Multi Disc Brake
Foot Brake		Mechanical Control
Parking Brake		Mechanical Control

TIRE OPTIONS

1st Option	front-rear	260/70R16 - 380/70R24
2nd Option	front-rear	260/70R18 - 380/70R28

DIMENSIONS

Total Length (Including Front Weights)	mm	3870
Total Height	mm	2157
Wheelbase	mm	2050
Front Track Width	mm	1340
Rear Track Width	mm	1285
Ground Clearance	mm	235-275

WEIGHTS

Tractor Weight (Without Additional Weight)	kg	3.000
Front Weights	kg	6x30+50
Rear Weights	kg	2x50