



BASAK



5105 *Red Power*



The photographs and the technical specifications used may include optional features.
BAŞAK Tractor reserves the right to modify the technical specifications in this brochure.

ASKO Sınai Ve Tek. San. Tic A.Ş BAŞAK Traktör Şube
Hanlı Sakarya Mh. Başak Sk No:65
Arifiye/SAKARYA/TÜRKİYE
Tel: +90 264 295 83 00
info@basaktraktor.com.tr



A MEMBER OF



f basaktraktortr

@ basaktraktor

in basaktraktor

x basaktraktortr

you basaktraktortr

www.basaktraktor.com.tr

www.asko.com.tr



ENGINE

Engine Type		DEUTZ TCD 2.9
Emission Level		EU STAGE V
Aspiration		Turbo-Intercooler
Cylinder Volume / Number of Cylinders	cm³/pcs	2,924/4
Maximum Engine Power	kW/hp/rpm	80/108/2000
Nominal Engine Power	kW/hp/rpm	75/102/2200
Maximum Engine Torque	Nm/rpm	400/1600
Air Filter Type		Pre-Cleaner 2 Stage Dry Air Filter
Injection System		Common Rail
Fuel / AdBlue Tank	L	120/20

TRANSMISSION

Gearbox Type		24+24 Mechanic
Shuttle		Mechanic Shuttle
4WD Control		Electro-Hydraulic
Front Differential Control Drive		Limited Slip
Rear Differential Control Drive		Electro-Hydraulic

HYDRAULIC SYSTEM

Maximum Oil Flow / Pump Pressure	lpm/bar	50/200
Functions		Electronic / (Mechanic Option)
Hydraulic Output	output/valve	8/4 (6/3 Option)
Maximum Rear Hitch Lifting Capacity	kg	3.400
Rear Hitch Remote Controls on Fenders		Option (Electronic / Mechanic)
Auto-Lift		Option (Electronic / Mechanic)

PTO SHAFT

Type		4 Speed PTO, Electro Hydraulically Controlled
PTO Speed		430-540-540E-1000
Front Linkage System		Option, Capacity 1.300 kg
Front Hydraulic Output	output/valve	Option, 2/1
Front PTO		Option, 6 Spline Multidisc Dry Clutch, With Sintered Friction Lining
Front PTO Speed	rpm	1000 CCW (@2000rpm Engine Speed)

BRAKES

Service Brake		Oil Immersed Multi Disc Brake
Foot Brake		Hydraulic Control
Parking Brake		Mechanical Control
Four Wheel Braking System		Standard

TIRE OPTIONS

1st Option	front-rear	340/85R24 - 460/85R30
2nd Option	front-rear	340/85R24 - 420/85R34
3rd Option	front-rear	340/85R24 - 340/85R38

WEIGHTS AND MEASURES

Tractor Weight (Without Additional Weight)	kg	4455-4750
Front Ballast Weight	kg	8x30+50
Rear Ballast Weight	kg	2x45
Total Length (Additional Weightless)	mm	4806
Wheelbase	mm	2400
Total Width	mm	2223
Total Height	mm	2768
Front Track Width	mm	1620
Rear Track Width	mm	1600
Ground Clearance	mm	362

ACCESSORIES

Battery Circuit Breaker		Standard
Hydraulic Top Link		Option
Air Compressor		Option
Pneumatic Trailer Brake		Option (Maximum Towable Mass 28 Tons)
Sunroof		Option
Cabin Suspension		Option
Pneumatic Seat		Option
Automatic Trailer Hitch		Option
Ledbar		Option
Rear View Camera		Option